



to each step casting as

tighten all hardware. DO NOT use flat washers!

indicated in this

drawing. Securely

WARNINGS!

- Do not over tighten the nuts and bolts or damage to the castings and or stripping of the threads could result.
- FOR SAFE AND PROPER USAGE OF THIS PRODUCT, THE MOUNTING INSTRUCTIONS MUST BE FOLLOWED CAREFULLY AND COMPLETELY.
- The manufacturer and distributor of this product are in no way responsible for the consumer's failure to adhere to the warnings and directions of these instructions in the event of damage to the consumer's vehicle, other properties and or personal injury.


MATERIAL NEEDED: Vehicle Application: Variable speed Drill Motor, cutting oil, RAM 5/16" drill bit (solid carbide), 3/16" drill '19-'22 1500 All Cabs/All doors bit (solid carbide), $2 - \frac{1}{2}$ " wrench/socket, **NEW BODY STYLE** 2 - 7/16" wrench/socket, center punch, hammer, marker or pencil, flat blade screw **Quality and Style that Endures** driver or 5/16" socket. WAX YOUR STEP ON A **REGULAR BASIS TO** Follow the diagram and the **MATERIAL FURNISHED:** MAINTAIN ITS LUSTER written directions carefully for Two step castings, four mounting brackets, instruction page and two hardware packs. (Not a proper, safe installation. all hardware may be used) Should you encounter an unusual, unforeseen problem, contact our Technical Help Carr Pattern Co., Inc. Warranty Policy Line Finishes: Limited Lifetime Structural Warranty: Limited Lifetime Warranty Conditions: 7:00 AM - 3:00 PM Pacific Time All warranties start from consumer's date of purchase. a. An warranties start from consumer's due to purchase. b. A new product will be sent out immediately to replace a warranty claim. c. The above guidelines apply only to the Original Purchaser. d. Original proof of purchase must be submitted for all warranty and returns issues. Warranty Limitations: a. Warranty coverage extends ONLY to repair or replacement of the CARR product. This warranty does not cover the cost of labore turns ensured of the product with a warranty does not cover the cost of labore turns ensured of the product. (951) 719-1068 Visit our web-site at www.CARR.com Warranty coverage does not extend to damage caused by: collision, fire, theft, freezing, vandalism, riot, explosion or object striking the product, or misuse of the product and/or the vehicle on which the product is being installed. Warranty coverage does not extend to damage caused by: airborne fallout (chemicals, tree sap, etc.), stones, hail, earthquake, water or flood, windstorm, lightning, the application of chemicals or sealants subsequent to manufacture. Warranty coverage does not extend to damages caused by: normal wear and tear, abuse, modification or improper Warranty Information c. on our website Carr Pattern Co., Inc. installation of the product. Warranty coverage does not extend to any economic loss or extra expense including (without limitation), payment for the loss of time or pay, inconvenience, storage, loss of vehicle use, vehicle rental expense, equipment rental expense, lodging, meals, or other travel costs **Other Terms:** 1. Using the $\frac{1}{4}$ " hardware provided, assemble the steel mounting brackets

Other Terms: This warranty gives you specific legal rights and you may also have other rights that vary from state to state. CARR does not authorize any person to create for it any other obligation or liability in connection with its products. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE APPLICABLE TO THIS PRODUCT IS LIMITED IN DURATION TO THE DURATION OF THIS WRITTEN WARRANTY. PERFORMANCE OF REPAIRS AND NEEDED ADJUSTMENTS IS THE EXCUSIVE REMEDY UNDER THIS WRITTEN WARRANTY OR ANY IMPLIED WARRANTY. CARR SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM BREACH OF THIS WRITTEN WARRANTY* *Some citede do not allow limitatione on how long an implicit ware party will lest or the archiving of incidentel or

*Some states do not allow limitations on how long an implied warranty will last or the exclusion or limitation of incidental or

consequential damages, so that above limitations or exclusions may not apply to you. **Guarantee:** Every attempt has been made to manufacture and distribute the finest quality products available. Our manufactured products are guaranteed to be free of defects due to workmanship or materials. Distributed products are subject to manufacturer's warranty only.

ALL DRAWINGS ARE VIEWED FROM THE DRIVERS SIDE





Super Hoop Step Installation Instructions Part No's: 129111 / 129112 / 129117

RAM '19-'22 1500 All Cabs/All Doors



ALL DRAWINGS ARE VIEWED FROM THE DRIVERS SIDE

2. Place each step in the position indicated in each drawing. Move the front door step so that the front steel FRONT DOOR mounting bracket is up against the three-bolt cluster. Move the rear door step against the other three-bolt cluster. Mark the bottom edge of the pinch weld where each hole center will be drilled. Transfer those marks REAR DOOR on the body metal referred to in the next step. 3. Transfer the marks from the previous using plenty of cutting oil, take a out at a slow speed the centered

> MARKED HORIZONTAL LINES 1/2" UP FROM **BOTTOM OF PINCH WELD**

- step and mark the front and rear step on the outside body metal as indicated on this drawing. Center punch marked lines. With the variable drill motor, 3/16" **solid carbide** drill bit and drill punched holes. Again, using plenty of cutting oil and at a slow speed, drill out the 3/16" hole with the 5/16" solid carbide drill bit.
- 4. Take the 5/16" hardware provided and securely mount the step assembly to the body of the vehicle. Do not use any flat washer under the 5/16" nylon nuts. Using the top 1/4" holes in each steel mounting bracket as a guide, drill out each hole with a 3/16" drill bit. Install the four sheet metals screws as indicated using the flat blade screwdriver or the 5/16 socket. Now your steps are ready to go! Repeat the same steps for the passenger side.

